

TEAGUE MINERAL PRODUCTS



TMP Custom Sealant Bentonite

TMP Custom Sealant Bentonite

is a high-swelling sodium bentonite of exceptional purity, and is not treated with polymers. Mined and processed in southeastern Oregon, it offers superior performance for use as a soil sealant. It forms impermeable barriers for ***sanitary landfills, hazardous waste sites, sewage lagoons, wetlands***, and other facilities.

Application rates primarily depend on the on-site soil and target hydraulic conductivity (permeability.) One or more permeameter and/or barrel tests using the on-site soil provide the best method of determining the correct ***TMP Custom Sealant*** - to soil mix. Proper mixing and compaction are essential for a good seal. Prehydration is necessary if the facility will hold fluids other than clean water.

These specifications and recommendations provide general guidelines only. They are not intended as a substitute for detailed engineering and specifications, which should be project specific.

TMP CUSTOM SEALANT
Sodium Bentonite



Certified to
NSF/ANSI 60

Specification and Typical Properties

- **Swell Index:**

2 gram sample (powder) in 100 ml water, aged 24 hours, minimum, 16 ml

- **Colloid Content:**

2% suspension, aged 24 hours, 85% - 95%

- **No Polymer Additives**

- **API Grit: Less than 1%**

- **API Yield:**

Minimum 80 barrels/ton

- **Semi-Granular Size:**

Up to 15% plus 20 mesh

Up to 20% minus 200 mesh

- **Cation Exchange Capacity:**

80 to 90 mill equivalents per 100 grams

- **Mineralogy by X-ray Diffraction:**

Smectite-85% - 95% Quartz, Feldspar, Calcite, Gypsum-less than 1% each.

- **Moisture Content:**

14%-16% TMP Bentonite is in its natural dry state at this moisture. Due to a smaller flake size, and a higher montmorillonite (clay) content, TMP bentonite has more retained water in its internal molecular structure than similar Wyoming types, while the bulk density is the same.

- **Approximate Weight:**

1,890—1998 lbs. per cubic yard

- **Certified:**

NSF Certified to NSF/ANSI 60

Teague Mineral Products, 1925 Hwy 201 S, Adrian, OR 97901

Phone: 541-339-3940 Fax: 541-339-4385 e-mail: info@teaguemineralproducts.com

© Copyright Teague Mineral Products. All rights reserved.